

# **C-Tec Predator**

### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: C-Tec Predator

OTHER NAMES: C-Tec Predator RECOMMENDED USE: Oven Cleaner

SUPPLIER NAME: 2CARE PRODUCTS
ADDRESS: 9 Donnor Place
Mt Wellington

Mt Wellington AUCKLAND

Phone: 0800 753 753 Fax: (09) 574 5999

Emergency Telephone: 0800 764 766 NEW ZEALAND NATIONAL POISON CENTRE

# 2. HAZARD(S) IDENTIFICATION

### **GLOBALLY HARMONISED SYSTEM**

HAZARD CLASSIFICATION HAZARDOUS according to the criteria of the Globally Harmonised System of Classification and

Labelling of Chemicals (GHS).

HAZARD CATEGORIES Corrosive to Metals Category 1

Skin Corrosion/Irritation Category 1B Serious Eye Damage/Irritation Category 1

**PICTOGRAMS** 



SIGNAL WORD DANGER

HAZARD STATEMENTS H290 – May be corrosive to metals.

H314 – Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

#### PRECAUTIONARY STATEMENTS

PREVENTION P102 – Keep out of reach of children.

P103 - Read label before use.

P104 – Read Safety Data Sheet before use. P234 – Keep only in original container.

P260 - Do not breathe fumes.

P264 – Wash hands thoroughly after handling.

P280 – Wear protective gloves, clothing and eye/face protection.

RESPONSE P101 – if medical advice is needed, have product container or label at hand.

P310 – IMMEDIATELY call a POISON CENTRE or Doctor/Physician.

P321 – IF SWALLOWED, give water to dilute and contact 111 immediately.

P363 – Wash contaminated clothing before re-use P390 – Absorb spillage to prevent material damage.

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 - IF ON SKIN: Remove all affected clothing IMMEDIATELY. Rinse skin with

water/shower.

P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously for several minutes. REMOVE contact lenses if

present and safe to do so. Continue rinsing.

STORAGE P405 – Store locked up.

P406 – Store in corrosive resistant plastic container with a resistant inner liner.

DISPOSAL P501 - Do not let this product enter the environment. Do not dispose of in waterways or sewers.

Dispose of this material and its container as hazardous waste, via a licensed facility. See local council

for disposal/recycling information.

### **ENVIRONMENTAL PROTECTION AUTHORITY (NEW ZEALAND)**

HSNO CLASSIFICATIONS Toxicity Hazards

8.1A Substances that are corrosive to metals.

8.2B Substances that are corrosive to dermal tissue UN PGII

8.3A Substances that are corrosive to ocular tissue.

The information contained in this SDS is specific to the product when handled and used neat. This product when diluted may not require the same control measures as the neat product. Check with your technical representative if in doubt.

POISONS SCHEDULE (AUS): S5

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

## Ingredients

Chemical Entity	Formula	CAS Number	Proportion
Sodium Hydroxide	NaOH	1310-73-2	< 5%
Other ingredients			< 5%
Water	H <sub>2</sub> O	7732-18-5	Balance

#### 4. FIRST AID MEASURES

INGESTION DO NOT induce vomiting. If person is conscious give water to drink immediately to dilute the caustic

soda. Seek **URGENT** medical attention.

EYE CONTACT IMMEDIATELY flush eyes with copious amounts of water for at least 30 minutes while holding

eyelids open. Take care not to rinse contaminated water into the non-affected eye. Washing must be started within 10 seconds of contact and continued for 30 minutes to prevent permanent injury.

Seek immediate medical attention. An Ophthalmology consultation is a must.

SKIN CONTACT REMOVE contaminated clothing. IMMEDIATELY flush the contaminated skin thoroughly with water

for at least 15 minutes. Seek medical attention **URGENTLY** if burning or irritation persists.

INHALATION Seek **URGENT** medical help. Remove victim from exposure to fresh air. Provide emergency airway

support. Give 100% humidified supplemental oxygen with artificial respiration. TRANSPORT to

emergency medical facility without delay.

SAFETY MEASURES Potable water should be available to rinse eyes or skin. Provide eye baths and safety showers. Treat

symptomatically.

PHYSICIAN NOTES For acute or short-term repeated exposures to highly alkaline materials:

Respiratory stress is uncommon but present occasionally because of soft tissue oedema. Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary. Oxygen is given as indicated. The presence of shock suggests perforation and mandates an intravenous line and fluid administration. Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue. Alkalis continue to cause damage after exposure.

Persons with lung diseases may be at an increased risk due to the toxic effects of this chemical on these organs.

## 5. FIRE FIGHTING METHODS

GENERAL MEASURES Clear fire area of all non-emergency personnel. Stay upwind. Keep out of low areas. Eliminate

ignition sources. Move fire exposed containers from fire area if it can be done without risk.

FLAMMABILITY CONDITIONS

Product is not combustible.

HAZARDOUS PRODUCTS OF

COMBUSTION

The product is non-combustible; however, the packaging material may burn to emit corrosive

fumes. Contact with metals may liberate hydrogen gas which is extremely flammable.

SPECIAL FIRE FIGHTING

INSTRUCTIONS

DO NOT allow firefighting water to reach waterways, drains or sewers. Store fire-fighting water for

treatment.

PERSONAL PROTECTIVE

**EQUIPMENT** 

Fire fighters should wear a positive-pressure self-contained breathing apparatus (SCBA) and protective fire-fighting clothing (includes fire-fighting helmet, coat, trousers, boots and gloves) or chemical splash suit. Please note: Structural fire fighters protective clothing is recommended for fire

situations only, it is not effective in spills.

HAZCHEM CODE 2W

# 6. SPILLAGE/ACCIDENTAL RELEASE MEASURES

GENERAL RESPONSE PROCEDURE

Clear area of all unprotected personnel. Allow only trained personnel wearing appropriate protective equipment to be involved in spill response. Contain spill, avoid accidents, clean up immediately. Increase ventilation. Avoid walking through spilled product as it is slippery when spilt. Use clean, non-sparking tools and equipment. Shut off all possible sources of ignition.

**CAUTION:** Contact with metals may liberate hydrogen gas which is extremely flammable.

**CLEAN UP PROCEDURES** 

Mechanically collect as much of the spill as possible. Absorb with sand, earth or clay. Transfer to suitable, labelled corrosion resistant containers and dispose of promptly as hazardous waste. Spill on areas other than pavement (e.g. dirt and sand) may be handled by removing the affected soils and placing in approved containers.

CONTAINMENT

Stop leak if safe to do so. Contain spill immediately.

**DECONTAMINATION** 

Dilute acid (preferably acetic acid may be used to neutralise residual traces of caustic soda) after

flushing.

ENVIRONMENTAL PRECAUTIONARY MEASURES Prevent run off into drains and waterways. If contamination of sewers or waterways has occurred

advise the Environmental Protection Authority and/or your local Waste Authority.

**EVACUATION CRITERIA** 

Evacuate all non-essential personnel.

PERSONAL PRECAUTIONARY MEASURES Personnel involved in the clean-up should wear full protective clothing as listed in section 8.

## 7. HANDLING AND STORAGE

**HANDLING** 

Ensure an eye bath and safety shower are available and ready for use. Observe good personal hygiene practices and recommended procedures. Wash thoroughly after handling. Avoid contact with eyes, skin and clothing. Do not inhale vapours. Avoid prolonged or repeated exposure. Do not smoke, eat or drink when handling product. Product can react violently with acids. Emergency showers and eye-washes must be available.

STORAGE

Store in a cool, dry, well-ventilated area. Keep containers tightly closed when not in use. Inspect regularly for deficiencies such as damage or leaks. Protect against physical damage. Store away from incompatible materials as listed in section 10. Store away from aluminium, tin, zinc and alloys (bronzes), chrome and lead. Protect from damp and kept apart from acids, halogenated hydrocarbons, nitroparaffins, etc. The floor must be waterproof and anti-slip. A water supply or source must be provided in the place of storage. Emergency showers and eye-washes must be available. Keep out of reach of children.

**CONTAINER** 

Store in original packaging as approved by manufacturer. Do not store in Aluminium or galvanised containers nor use die cast zinc or aluminium fittings (e.g. valves and bungs.)

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

GENERAL Sodium Hydroxide – [CAS 1310-73-2]

EXPOSURE LIMITS TWA-Ceiling 2mg/m³ from New Zealand Workplace Exposure Standards.

Printed: 9 January 2018 30073 - C-TEC PREDATOR - 140817 Page 4 of 8

BIOLOGICAL LIMITS No information available on biological limit values for this product.

ENGINEERING MEASURES A system of local and/or general exhaust is recommended to keep employee exposures as low as

possible. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Adequate

ventilation should be provided so that exposure limits are not exceeded.

PERSONAL PROTECTIVE

**EQUIPMENT** 

RESPIRATOR If determined an inhalation risk is present. Use a P2 grade disposable mask which

conforms to the requirements of AS1715/1716).

EYES Use splash proof safety goggles, and/or if necessary an appropriate full-face

shield that conform to AS1336/1337.

HANDS Any Gloves approved for chemical hazards that conform to AS2161.

CLOTHING Trousers, Long sleeved shirt and closed shoes.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

PHYSICAL STATE Liquid

APPEARANCE Free flowing

COLOUR Red

ODOUR Odourless

pH 14.0

DENSITY

No Data Available

VAPOUR PRESSURE

No Data Available

VAPOUR DENSITY

No Data Available

BOILING POINT

No Data Available

FREEZING POINT

No Data Available

SOLUBILITY

Complete in water

SHELF LIFE 2 years from manufacturing date (when stored as directed)

# 10. STABILITY AND REACTIVITY

Issue Date: 14th August 2017

GENERAL INFORMATION Corrosive Liquid.

CHEMICAL STABILITY The substance is stable under normal environmental and foreseeable conditions of temperature and

pressure during storage and handling.

CONDITIONS TO AVOID Avoid contact with foodstuffs. Do not combine part drums of the same product.

MATERIALS TO AVOID Highly exothermic reaction with strong acids, aluminium, tin, zinc and their alloys, copper, lead, etc,

acetic acid, allyl chloride, chlorine trifluoride, chloroform, methylic alcohol, chloronitrotoluene, chlorosulphonic acid, glyoxal, cyanohydrin, hydrochloric acid, hydrofluoric acid, hydroquinone, nitric acid, sulphuric acid and oleum, nitropropane, phosphorous, propiolactone, phosphorous pentoxide,

 $tetrachlorobenzene, tetrahydrofuran, nitromethane \ and \ nitroparaffins.$ 

Caustic soda solutions may react readily with various reducing sugars (i.e.: fructose, galactose,

maltose, dry whey solids) to produce carbon monoxide.

Printed: 9 January 2018 30073 - C-TEC PREDATOR - 140817

HAZARDOUS DECOMPOSITION PRODUCTS The packaging material may burn to emit noxious fumes. Reacts with aluminium, tin, zinc and their alloys, copper, lead, etc. giving off hydrogen. When the product decomposes, toxic sodium oxide gases are given off.

#### 11. TOXICOLOGICAL INFORMATION

ORAL Sodium Hydroxide – LD<sub>LO</sub> – 500mg/kg (Rabbit 24hr).

Causes severe burns. Burns to the mouth, oesophagus, can cause intestinal perforation.

DERMAL Sodium Hydroxide – LD<sub>LO</sub> – 500mg/24hr (Rabbit).

Causes severe burns. Intense burning and ulcers penetrating the skin.

INHALATION Causes severe burns. Irritation of the respiratory system.

EYE Sodium Hydroxide – LDLO – 50mg/24hr (Rabbit)

Causes serious eye damage. Can cause ulceration of the conjunctiva and cornea.

CARCINOGENICITY The substance did not induce mutagenicity in in vitro and in vivo studies (EU RAR, 2007). Systemic

carcinogenicity is not expected to occur because the substance is not expected to be systemically

available in the body under normal handling and use conditions.

MUTAGENICITY Both the in vitro and the in vivo genetic toxicity tests indicated no evidence of mutagenic activity.

Furthermore, the substance is not expected to be systemically available in the body under normal handling and use conditions and for this reason additional testing is considered unnecessary (EU

RAR, 2007).

REPRODUCTIVE The substance is not expected to be systemically available in the body under normal handling and

use conditions and for this reason it can be stated that the substance will not reach the foetus nor

reach male and female reproductive organs

TARGET ORGAN Repeated exposure: Corrosive substance. In addition, the substance is not expected to be

systemically available in the body under normal handling and use conditions and therefore systemic

effects of the substance after repeated exposure are not expected to occur.

LONG TERM No information available.

### 12. ECOLOGICAL INFORMATION

ECOTOXICITY Sodium Hydroxide  $LC_{50} - 45.4$ mg/L (Onchorhyncus mykiss - 96hr).

 $EC_{50} - 40.38$ mg/L (Ceriodaphnia dubia – 48hr).

PERSISTENCE / Readily biodegradable.

DEGRADABILITY Other relevant information Abiotic degradation: NaOH is a strong alkaline substance that dissociates

completely in water to Na<sup>+</sup> and OH<sup>-</sup>. High water solubility and low vapour pressure indicate that NaOH will be found predominantly in aquatic environment. This implies that it will not adsorb on particulate matter or surfaces. Atmospheric emissions as aerosols are rapidly neutralized by carbon

dioxide and the salts will be washed out by rain.

MOBILITY High water solubility and mobility.

ENVIRONMENTAL FATE Do not allow drainage into sewer, streams or storm water systems.

Issue Date: 14<sup>th</sup> August 2017 Printed: 9 January 2018 Page 6 of 8

30073 - C-TEC PREDATOR - 140817

**BIOACCUMULATION** 

POTENTIAL

Sodium Hydroxide does not bioaccumulate in organism. In addition, sodium is a naturally occurring element that is prevalent in the environment and to which organism are exposed regularly for which

they have some capacity to regulate the concentration in the organism.

ENVIRONMENTAL IMPACT No information available.

#### 13. DISPOSAL CONSIDERATIONS

GENERAL INFORMATION Dispose of in accordance with all local, regional and national regulations. All empty packaging should

be disposed of in accordance with local, regional, and national regulations or recycled/reconditioned

at an approved facility.

**SPECIAL PRECAUTIONS** 

FOR LANDFILL

Containers should be triple rinsed then rinsed with dilute hydrochloric acid to neutralise sodium/potassium hydroxide residues which should be added slowly by trained staff wearing proper

protection.

Disposal of this product must comply with any requirements of the Resource Management Act for

which approval should be sought from the Regional Authority.

#### 14. TRANSPORT INFORMATION

# LAND TRANSPORT NEW ZEALAND (NZS5433)

Classified as a Dangerous Good by NZS5433:2012 for transport by Road and Rail

PROPER SHIPPING NAME CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S (Contains Sodium Hydroxide)

UN NUMBER 3266

CLASS 8 – Corrosive Substances
SUBSIDIARY RISK No Data Available

PACKAGING GROUP II HAZCHEM 2W

EPG 37 Toxic and/or Corrosive Substances Non-Combustible

SPECIAL PROVISIONS No Data Available

### **SEA TRANSPORT (IMDG)**

Classified as a Dangerous Good by the International Maritime Dangerous Good Code (IMDG) for transport by sea.

PROPER SHIPPING NAME CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S (Contains Sodium Hydroxide)

UN NUMBER 3266

CLASS 8 – Corrosive Substances
SUBSIDIARY RISK No Data Available

PACKAGING GROUP II
HAZCHEM 2W
EMS F-A, S-B

MARINE POLLUTANT No Data Available SPECIAL PROVISIONS No Data Available

#### **AIR TRANSPORT (IATA)**

Classified as a Dangerous Good by the international Air Transport Association (IATA) for transport by air

PROPER SHIPPING NAME CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S (Contains Sodium Hydroxide)

UN NUMBER 3266

CLASS 8 – Corrosive Substances
SUBSIDIARY RISK No Data Available

PACKAGING GROUP II HAZCHEM 2W

EPG 37 Toxic and/or Corrosive Substances Non-Combustible

SPECIAL PROVISIONS No Data Available

Issue Date: 14<sup>th</sup> August 2017 Printed: 9 January 2018 30073 - C-TEC PREDATOR - 140817

Page 7 of 8

#### 15. REGULATORY INFORMATION

#### **ENVIRONMENTAL PROTECTION AUTHORITY (NEW ZEALAND)**

Hazardous Substances & New Organisms Act 1996

APPROVAL CODE HSR002526 – Cleaning Products (Corrosive) Group Standard 2006

HSNO CLASSIFICATIONS 8.1A, 8.2B, 8.3A,
APPROVED HANDLER Not Required

NZIOC Listed

#### 16. OTHER INFORMATION

REVISION NUMBER 1 – New Issue ISSUE DATE 14<sup>th</sup> August 2017

In any event the review and if necessary re-issue of an SDS shall be no longer than 5 years after the last date of issue.

KEY/LEGEND AS1336/1337 Industrial Eye Protection – Metric Units (Standards Australia).

AS1715/1716 Respiratory Protection Devices – Metric Units (Standards Australia).

AS2161 Industrial Safety Gloves and Mittens (Standards Australia).

CAS Chemical Abstracts Service.

EC<sub>50</sub> Concentration which induces a response halfway between the baseline and

naximum.

EMS IMDG Emergency Schedule.
EPG Emergency Procedures Guide.
GHS Globally Harmonised System.

HSNO Hazardous Substances and New Organisms.

IMDG International Maritime Dangerous Goods.

LC<sub>50</sub> Concentration required to kill half the members of a tested population after a

specified duration.

LD<sub>50</sub> Dosage required to kill half the members of a tested population after a specified

duration.

 $LD_{LO}$  Lowest dosage required to produce death in a given species under controlled

conditions.

NOEC No Observed Effect Concentration.

NZIOC New Zealand Inventory of Chemicals.

SDS Safety Data Sheet.
UN No. UN Nations Number.

WES-Ceiling Concentration that should not be exceeded at any time during any part of the

working day.

REFERENCES Workplace Exposure Standards-and Biological Exposure Indices – WorkSafe New Zealand.

TOXNET - ChemIDPlus Database.

IMDG Appendix B List of Marine Pollutants. IMDG Emergency Fire and Spill Codes.

UN Recommendations on the Transport of Dangerous Goods Volume 1 (17th Edition) Part 3.

This SDS has been prepared from current technical data and summarises at the date of issue our best knowledge of the health and safety information of the product, and in particular how to safely handle and use the product in the work place. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact the company.

Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.

This SDS may only be reproduced in full. Summaries or excerpts from this SDS may not contain all the relevant information and thus are not permitted.

Issue Date: 14<sup>th</sup> August 2017 Printed: 9 January 2018 Page 8 of 8
30073 - C-TEC PREDATOR - 140817